

TECHNICAL SPECIFICATIONS

Model:	Type B, Type D
Weapon type:	Semi-automatic pistol, striker-fired
Caliber:	9 mm Luger
Locking System:	Recoil operated, with vertical locking block – AF-Speedlock™
Length (overall):	Standard Barrel 196 mm (7,7") Threaded Barrel 214 mm (8,4")
Height (overall):	132.6mm (5.2")
Width (overall):	36.1 mm (1,4")
Weight (with empty magazine):	840 g (29,6 oz.)
Distance Hand-Barrel Axis:	12 mm
Barrel:	- 109 mm (4,3"), 6 grooves, right-hand twist 1:10 (for the standard barrel) - 127 mm (5"), 6 grooves, right-hand twist 1:10 (for the threaded barrel)
Barrel threads:	½-28" or 13,5×1 LH thread
Barrel Rifling:	1:10RH
Barrel Crown:	45DEG
Magazine capacity:	16 cartridges, double stack (compact magazine body) 19 cartridges, double stack (long magazine body)
Trigger:	Single action, pre-cocked
Trigger Pull:	5 LBS.
Safety:	Trigger safety, firing pin safety
Sights:	Fixed, replaceable
Sight Radius:	165MM (6.5")
Front Sight Height:	5.2-7.6 (.205-.300) depends on 1-9 graduation table for adjusting; always 1.6mm (.063) from top to center of fiberoptic.
Front Sight Width:	3.2mm (.126")
Rear Sight Width:	18mm (.708")
Rear Sight U Notch Width:	3.2 (.126") square
Optic Footprint Options:	Shield Footprint + Cover Plate, Aimpoint Acro P2
Materials:	Steel (slide, barrel, frame), polymer (pistol grip)
Accessory Rail:	PICCATINY